

Komet Desktop Payphone

Featuring the Series 5-XG

Product Features:

- o Utilizes QuorTech's **Series 5-XG** board with **Poll Quest** or **PNM Plus** management software, a **proven leader** in the industry
- o **MS-16** family **Electronic Coin Validator** for accurate acceptance of 6 denominations of coins or tokens
- o **Backlit LCD** with easy to read **text prompts** in Both Spanish and English
- o Spanish & English **digital voice prompts**.
- o **Easy connectivity** to external **Fixed Wireless Terminal (FWT)** for call flexibility
- o **Payphone Management system** Poll Quest and PNM Plus is PC based using Windows platform.
- o **Remote programming** and uploading of statistics, alarms and cashbox totals.
- o Built in **Volume Control**.
- o **Heavy-Duty steel** construction.
- o **One-year warranty** on S5-XG board, 90-day warranty on hardware.



Contact Al Quiros for more information:
Telephone +941-870-4721
Email: aquiros@quortech.com

Specifications:

- o Power Requirements: Telephone line powered, 30VDC (on hook), 23 mA loop current (off hook)
- o Internal rechargeable lead-acid gel cell, 6V, 1.2 AH
- o Operating Temperature Range:-4 to +140 Degrees Fahrenheit
- o Relative Humidity Range: 0% to 95% non-condensing
- o Grounding Requirement: Earth ground
- o Surge Protector: On-board solid-state transient surge protector on telephone line
- o Telco line type: COCOT (PAL) B-1, Loop Start
- o Loop Current Range: 23 mA to 80 mA
- o Coin Relay Driver: Internally provided +/- 80 VDC (COCOT B-1)
- o Voice Prompts: High quality digitally-recorded female voice.
- o Dimensions: 36.8cm X 25.5cm X 23cm
- o Weight: 25 lbs

Compliances:

- o Complies with Part 68 and Part 15 of the US Federal Communications Commission Rules and Regulations and is in general compliance with all requirements described in applicable CCITT recommendations.
- o Ringer Equivalency Number (REN):1.0 B
- o FCC Registration Number: E2DUSA-32134-CX-E
- o Telco Line Interface: Internal to payphone, RJ11C jack on printed circuit board.
- o Modem: 2400 baud, conforms to BellCore 212A specifications

